Declaration of performance

Number:

Rijswaard facing brick



(4) Manu	facturer:
----------	-----------

 Steenfabriek De Rijswaard B.V.
 Tel: +31 (0)418 - 55 22 21

 De Rijswaard 2
 Fax: +31 (0)418 - 55 29 00

 NL-5308 LV AALST
 www.rijswaard.nl



(1) Unique identification code of the product- type	Geel/Naturel
(2) Typenumber	202022011 Beige Stock / DR52B
(3) Intended use or uses of the construction productbouwproduct	Units for use in unprotected masonry walls, colums and partitions.
(6) System or systems of assessment and verification of constancy of performance of the construction product	2+
(7) Notified body	Notified Body KIWA 0620-CPD performed under system 2+ the initial inspection of the manufacturing plant and of the factory production control, performed the continuous surveillance, assessment and evaluation of the factory production control and issued the certificate of conformity of the factory production control.

EF 215x100x65		-
217	mm	
102	mm	
64	mm	
T2		
R1		U Metselbaksteen, Categorie I volgens EN771- 1:2011 + A1:2015
NPD		
NPD		
1450	kg/m3	
NPD	kg/m3	
DM ±15	%	
<20%		1
1		
≥ 15	N/mm2	
≥ 15	N/mm2	
0.15 / 0.30		
50/50: 0.41 / 90/90: 0.45	W/mK	EN 1745:2012
5/10		
F2		1
≤ 24 %	m/md	
<8	kg/(m²min)	1
S2		
NPD	mm/m	1
Voldoet		NL-BBK
	102 64 T2 R1 NPD NPD 1450 NPD 1450 NPD DM ±15 <20% 1 ≥ 15 ≥ 15 0.15 / 0.30 50/50: 0.41 / 90/90: 0.45 5/10 F2 ≤ 24 % <8 S2 NPD	102 mm 64 mm T2 R1 NPD NPD 1450 kg/m3 NPD kg/m3 DM ±15 % <20% 1 ≥ 15 N/mm2 ≥ 15 N/mm2 ≥ 15 N/mm2 50/50: 0.41 / 90/90: 0.45 W/mK 5/10 F2 ≤ 24 % m/md <8 kg/(m²min) S2 NPD mm/m

(10) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of perfomance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behiaf of the manufacturer by

Atse Blei General Management

Aalst (NL) 21-Mar-2024